

# OJK-V

## STEPP Oil Jacketed Kettle



12325 River Road / North Branch MN 55056 ~ P: 651-674-4491 F: 651-674-4221 ~ jason@steppmfg.com ~ branda@steppmfg.com

The Stepp MFG Oil Jacketed Vertical Kettle (double boiler) is used to melt rubberized crack sealing and water proofing compounds and apply them to the road surface. The OJK-V Kettle sealer is trailer mounted and completely self contained. The OJK-V is capable of heating, melting, and applying all grades of rubberized asphalt crack sealer, joint sealants, and waterproofing compounds without the need for additional equipment. The OJK-V is capable of heating sealing material from ambient temperature to application temperature in 60 minutes or less.

### Available Sizes...

- OJK 75 Gallon
- OJK125 Gallon

### Design Benefits...

- LP or Diesel Burner System
- Heavy Duty Construction
- Vertical Agitator
- Gravity Discharge
- Center Heat Riser



### Options...

- Pumping System
- Overhead Boom
- "Exact Flow" Wand
- Air Compressor
- Overnight Heat
- Agitator Shut Down
- Heated Hose
- Strobe light
- "Pump Saver" On Demand Pumping System
- Detailed specifications available upon request.



VISIT US ONLINE AT:

[www.steppmfg.com](http://www.steppmfg.com) OR <https://www.facebook.com/steppmfg>

<b>Quick Specs</b>	<b>OJK 75</b>	<b>OJK 125</b>
Material Capacity	75 Gallons	125 Gallons
Empty Weight	3,000 lbs.	3,500 lbs.
GVWR	Single Axle 6,000 lbs.	Single Axle 6,000 lbs.
Dimensions (LxWxH)	128"x 73"x 88"	148"x 73"x 96"
Loading Height	48"	53"
Diesel Burner BTU	120,000 BTU	120,000 BTU
LP Burner BTU	250,000 BTU	250,000 BTU
Fuel Tank Capacity	25 Gallons	25 Gallons
Hydraulic Tank Capacity	19 Gallons	19 Gallons
Tank Construction	10 Gauge Tank 10 Gauge Oil Jacket 12 Gauge Insulation	10 Gauge Tank 10 Gauge Oil Jacket 12 Gauge Insulation
Tank Configuration	Vertical	Vertical
Frame Construction	2"x 4"x 11 ga Rectangular Steel Tubing	2"x 4"x 11 ga Rectangular Steel Tubing
Heat Transfer Oil	ISO 460 with 550°F C.O.C. Flash Point	ISO 460 with 550°F C.O.C. Flash Point
HTO Capacity	28 Gallons	30 Gallons
Tires	(2) ST225/75R15	(2) ST225/75R15
Brakes	Electric (std) Hydraulic (opt)	Electric (std) Hydraulic (opt)
Hitch	3" Pintle or 2-5/16" Ball	3" Pintle or 2-5/16" Ball
Hitch Height	Adjustable 24"-32"	Adjustable 24"-32"