

SGS FLUE FIRED KETTLES

12325 River Road / North Branch MN 55056 ~ P: 651-674-4491 F: 651-674-4221 ~ jason@steppmfg.com ~ branda@steppmfg.com

Stepp SGS Flue Fired Kettles are designed to heat and apply various bitumen's and emulsions for crack filling and seal coating.

Available Sizes...

- SGS 180 gallon
- SGS 275 gallon
- SGS 360 gallon
- SGS 580 gallon

Design Benefits...

- Automatic Temperature Controls
- LP Gas or Diesel Burners
- Hydraulic Powered Submerged Pumping System

Options...

- 6' or 8' spray bars
- Heated spray hoses and wands
- Overnight heaters
- Agitation
- Safety Loading Chute
- Traffic Arrowboard
- Fire Extinguisher
- Detailed specifications available upon request.



VISIT US ONLINE AT:

www.steppmfg.com OR <https://www.facebook.com/steppmfg>

Quick Spec	SGS 180	SGS 275	SGS 360	SGS 580
Material Capacity	180 Gallons	275 Gallons	360 Gallons	580 Gallons
Empty Weight	2,000 lbs.	2,000 lbs.	3,200 lbs.	4,000 lbs.
GVWR	3,500 lbs.	6,000 lbs.	6,000 lbs.	12,000 lbs.
Dimensions (LxWxH)	155"x 77"x 102"	182"x 76"x 71"	196"x 72"x 62"	240"x 86"x 60"
Diesel Burner BTU	500,000 BTU	500,000 BTU	500,000 BTU	500,000 BTU
LP Burner BTU	500,000 BTU	500,000 BTU	500,000 BTU	500,000 BTU
Frame Construction	2"x 4"x 11 ga Rectangular Steel Tubing	2"x 5"x 11 ga Rectangular Steel Tubing	2"x 6"x 3/16" Rectangular Steel Tubing	2"x 6"x 3/16" Rectangular Steel Tubing
Tires	225/75R15	225/75R15	235/80R16	225/75R15
Axles	Single 3,500 lbs.	Single 6,000 lbs.	Single 6,000 lbs.	Tandem 6,000 lbs.
Brakes	Electric (std) Hydraulic (opt)	Electric (std) Hydraulic (opt)	Electric (std) Hydraulic (opt)	Electric (std) Hydraulic (opt)
Hitch	3" Pintle or 2-5/16" Ball	3" Pintle or 2-5/16" Ball	3" Pintle or 2-5/16" Ball	3" Pintle or 2-5/16" Ball
Hitch Height	Adjustable 24"-32"	Adjustable 24"-32"	Adjustable 24"-32"	Adjustable 24"-32"