

# **SBF** **BOTTOM FIRED KETTLES**

12325 River Road / North Branch MN 55056 ~ P: 651-674-4491 F: 651-674-4221 ~ jason@steppmfg.com ~ branda@steppmfg.com

Stepp SBF Bottom Fired Kettles are designed to heat and apply various bitumen's and emulsions for crack filling and seal coating.

## **Available Sizes...**

- SBF 200 Gallon
- SBF 300 Gallon
- SBF 500 Gallon

## **Design Benefits...**

- Automatic Temperature Controls
- LP Gas or Diesel Burners
- Hydraulic Powered Submerged Pumping System

## **Options...**

- 6' or 8' spray bars
- Heated spray hoses and wands
- Overnight heaters
- Agitation
- Safety Loading Chute
- Traffic Arrowboard
- Fire Extinguisher
- Detailed specifications available upon request.



VISIT US ONLINE AT:

[www.steppmfg.com](http://www.steppmfg.com) OR <https://www.facebook.com/steppmfg>

<b>Quick Spec</b>	<b>SBF 200</b>	<b>SBF 300</b>	<b>SBF 500</b>
Material Capacity	200 Gallons	300 Gallons	500 Gallons
Empty Weight	2,500 lbs.	5,100 lbs.	5,500 lbs.
GVWR	6,000 lbs.	6,000 lbs.	12,000 lbs.
Dimensions (LxWxH)	175"x 100"x 94"	218"x 95"x 87"	222"x 96"x 79"
Diesel Burner BTU	500,000 BTU	500,000 BTU	500,000 BTU
LP Burner BTU	500,000 BTU	500,000 BTU	500,000 BTU
Frame Construction	2"x 4"x 11 ga Rectangular Steel Tubing	2"x 5"x 11 ga Rectangular Steel Tubing	2"x 6"x 3/16" Rectangular Steel Tubing
Tires	225/75R15	235/80R16	225/75R15
Axles	Single 6,000 lbs.	Single 6,000 lbs.	Tandem 6,000 lbs.
Brakes	Electric (std) Hydraulic (opt)	Electric (std) Hydraulic (opt)	Electric (std) Hydraulic (opt)
Hitch	3" Pintle or 2-5/16" Ball	3" Pintle or 2-5/16" Ball	3" Pintle or 2-5/16" Ball
Hitch Height	Adjustable 24"-32"	Adjustable 24"-32"	Adjustable 24"-32"